IN THE CLAIMS

The text of all pending claims, along with their current status, is set forth below:

- 35. (currently amended) A method of forming solder balls, the method comprising the acts of:
- (a)—disposing solder within a plurality of receptacles disposed within a surface of a conveyor belt; and
 - (b)—heating the solder disposed within the receptacles to form a solder ball within each receptacle.
- 54. (previously presented) The method as recited in claim 35, wherein disposing solder within the plurality of receptacles comprises disposing solder within the plurality of receptacles formed by a first portion of the conveyor belt having a plurality of holes disposed upon a second portion of the conveyor belt.
- 55. (previously presented) The method as recited in claim 35, wherein disposing solder comprises using a squeegee positioned adjacent to the surface of the conveyor belt to deposit solder within the receptacles.
- 56. (previously presented) The method as recited in claim 35, wherein disposing solder within the plurality of receptacles comprises disposing solder within non-wettable receptacles.

- 57. (previously presented) The method as recited in claim 35, wherein disposing solder within the plurality of receptacles comprises disposing solder within receptacles of uniform volume.
- 58. (previously presented) The method as recited in claim 35, wherein disposing solder within the plurality of receptacles comprises disposing solder within receptacles of uniform size.
- 59. (previously presented) The method as recited in claim 35, wherein each of the plurality of receptacles have a width greater than a diameter of the solder ball formed within each respective receptacle.
- 60. (previously presented) The method as recited in claim 35, wherein the conveyor belt comprises one of stainless steel and titanium.
- 61. (previously presented) The method as recited in claim 35, wherein heating the solder disposed within the receptacles comprises moving the conveyor belt along a given path through a furnace.
- 62. (previously presented) The method as recited in claim 35, further comprising cleaning the solder balls with a cleaning device positioned downstream of the heating device.
- 63. (previously presented) The method as recited in claim 35, further comprising transferring the solder balls from the conveyor belt to a catch basin positioned downstream of the heating device.

U.S. Application Serial No. 10/630,051 Response to Office Action dated June 16, 2004

- 64. (previously presented) The method as recited in claim 35, further comprising removing the solder balls from the conveyor belt.
- 65. (previously presented) The method as recited in claim 64, wherein removing the solder balls comprises vibrating the conveyor belt to discharge the solder balls from the conveyor belt.